

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) An assembly defining longitudinal, lateral, and transverse directions substantially orthogonal to one another, the assembly comprising;

a connection box having a proximal end shaped to receive a fastener to support the connection box and a distal end, spaced in the lateral direction from the proximal end and having a stop and a slide;

a spacer shaped to insert exclusively by linear translation, without tools, within the slide to the stop;

the spacer extending from the proximal ~~proximal~~ distal end to support the connection box in the transverse direction when inserted into the slide against the stop; and

the spacer having at least one fracture region providing controlled fracture, in response to bending stress, to adjust the length thereof.

2. (currently amended) The assembly of claim 1, wherein the stop extends in the lateral direction from the an exterior surface of the distal end of the connection box to register the connection box with respect to a wall panel.

3. (previously presented) The assembly of claim 2, wherein the slide is positioned on the exterior surface of the distal end of the connection box.

4. (previously presented) The assembly of claim 1, wherein the connection box is further provided with an aperture to receive transmission lines from a signal source and terminating therewithin.

5. (original) The assembly of claim 4, wherein the connection box is a multi-gang connection box.

6. (original) The assembly of claim 5, wherein the connection box is homogeneously molded of a material selected from the group consisting of a polymer and a reinforced polymer.

7. (cancelled)

8. (currently amended) The assembly of claim 6, wherein the ~~the~~ at least one fracture region comprises a source of a stress concentration riser.

9. (original) The assembly of claim 8, wherein the source of stress concentration riser comprises a scored line extending across the spacer.

10. (cancelled)

11. (previously presented) The assembly of claim 9, wherein the spacer is homogeneously molded of a material selected from the group consisting of a polymer and a reinforced polymer.

BEST AVAILABLE COPY

12. (original) The assembly of claim 11, wherein the slide has a frictional engagement with the spacer providing a resistance value selected to resist inadvertent removal of the spacer from the slide.

13. (original) The assembly of claim 12, wherein the spacer comprises an extension portion projecting in the transverse direction from proximate the connection box to a foot portion extending in at least one of the lateral direction and longitudinal direction to resist penetration of the spacer into a solid material positioned thereagainst.

14. (original) The assembly of claim 13, wherein the scored line is positioned on the spacer to promote fracture at a location selected to space the foot from the stop a distance corresponding to the width of a building stud of a first standard size.

15. (original) The assembly of claim 14, wherein the extension has an unbroken length selected to space the foot from the stop a distance corresponding to the width of a building stud of a second standard size.

16. (withdrawn) The assembly of claim 15, further comprising a fixture for delivery of a signal to a consuming device.

17. (withdrawn) The assembly of claim 16, further comprising an anchor, removably secured to the fixture and having a first engagement mechanism;

18. (withdrawn) The assembly of claim 17, wherein the connection box further comprises a receiver to receive the anchor and having a second engagement mechanism to engage the first engagement mechanism without tools.

19. (withdrawn) The assembly of claim 18, wherein the connection box is generally rectangular in shape, having an open face on one side thereof.

20. (withdrawn) The assembly of claim 19, wherein the stop registers the open face of the connection box.

21. (currently amended) The assembly of claim 15, wherein the the building stud of a first standard size comprises a two-by-four and the building stud of a second standard size comprises a two-by-six.

22. (original) The assembly of claim 1, wherein the connection box is further provided with an aperture to receive transmission lines from a signal source and terminating therewithin.

23. (original) The assembly of claim 1, wherein the connection box is a multi-gang connection box.

24. (original) The assembly of claim 1, wherein the connection box is homogeneously molded of a material selected from the group consisting of a polymer and a reinforced polymer.

25. (cancelled)

26. (currently amended) The assembly of claim 1, wherein the ~~the~~ at least one fracture region comprises a source of a stress concentration riser.

27. (original) The assembly of claim 26, wherein the source of stress concentration riser comprises a scored line extending across the spacer.

28. (cancelled)

29. (original) The assembly of claim 1, wherein the spacer is homogeneously molded of a material selected from the group consisting of a polymer and a reinforced polymer.

30. (original) The assembly of claim 1, wherein the slide has a frictional engagement with the spacer providing a resistance value selected to resist inadvertent removal of the spacer from the slide.

BEST AVAILABLE COPY

31. (original) The assembly of claim 1, wherein the spacer comprises an extension portion projecting in the transverse direction from proximate the connection box to a foot portion extending in at least one of the lateral direction and longitudinal direction to resist penetration of the spacer into a solid material positioned thereagainst.

32. (currently amended) The assembly of claim 31, wherein the at least one fracture region comprises a scored line positioned on the spacer to promote fracture at a location selected to space the foot portion from the stop a distance corresponding to the width of a building stud of a first standard size.

33. (currently amended) The assembly of claim 32, wherein the extension portion has an unbroken length selected to space the foot portion from the stop a distance corresponding to the width of a building stud of a second standard size.

34. (withdrawn) The assembly of claim 1, further comprising a fixture for delivery of a signal to a consuming device.

35. (withdrawn) The assembly of claim 34, further comprising an anchor, removably secured to the fixture and having a first engagement mechanism;

36. (withdrawn) The assembly of claim 35, wherein the connection box further comprises a receiver to receive the anchor and having a second engagement mechanism to engage the first engagement mechanism without tools.

37. (withdrawn) The assembly of claim 36, wherein the connection box is generally rectangular in shape, having an open face on one side thereof.

38. (withdrawn) The assembly of claim 37, wherein the stop registers the open face of the connection box.

BEST AVAILABLE COPY

39. (currently amended) A connection box assembly defining longitudinal, lateral, and transverse directions substantially orthogonal to one another, the assembly ~~comprising~~; comprising:

a connection box having an aperture shaped to receive transmission lines to terminate therewithin, having a proximal end provided with an aperture to receive a fastener to support the connection box, and having a distal end, spaced in the lateral direction from the proximal end and formed to have a stop and a slide;

a spacer matingly insertable into the slide, without the use of tools, to engage the stop and sized to frictionally engage the slide to resist removal therefrom;

the spacer having at least one fracture region extending longitudinally thereacross to provide directed stress concentration fracture in response to bending, to adjust the length thereof; and

the spacer extending from the proximal distal end of the connection box in the transverse direction when inserted into the slide and abutted against the stop.

BEST AVAILABLE COPY



40. (previously presented) A method for applying a connection box to a structural member defining longitudinal, lateral, and transverse directions substantially orthogonal to one another, the method comprising:

providing a connection box having a proximal end and a distal end spaced from one another, the distal end having a stop and a slide;

selecting a structural member extending in the longitudinal direction and having a width in the transverse direction;

providing a spacer shaped to be received by the slide and characterized by a length;

fracturing the spacer to adjust the length thereof to correspond to the width of the structural member;

securing the spacer to the connection box without the use of tools by inserting the spacer within the slide until the spacer contacts the stop; and

securing the proximal end of the connection box to the structural member.

BEST AVAILABLE COPY